



## **ES900 UPRIGHT**

TECHNICAL SPECIFICATIONS	Power Source	110V/15A
	Cord Length	8¹ (2.4M)
	Drive Motor	Single Stage Drive System with Poly-V Belts
	Crank	3-Piece Forged Steel Crank System with Sealed Bearings
	Resistance Source	Eddy Current Brake
	Resistance Levels	25 (Emerge), 30 (Escalate°)
	Workload Range	40-450 Watts
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Pedals	Dual Sided and Weighted with Integrated Ratcheting Strap
	Seat	Gel Seat with Fore/Aft Seat Adjustments
	Handlebar Design	Multi-Position with Moisture Resistant Sleeves
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
AVAILABLE CONSOLES		Escalate <sup>9</sup> , Emerge
SAFETY	White are a second	Low Step Over Height
REGULATORY APPROVALS		ETL UL1647, CSA
EXTRAS	Accessories	Water Bottle Holder (2, removable), Accessory Tray, Over Molded Reading Rack/Tablet Holder
PHYSICAL SPECIFICATIONS	Footprint	44"L x 24"W (111 cm x 61 cm)
	Machine Weight	122 lbs. (56 kg)
	Maximum User Weight	350 lbs. (159 kg)
	Step-Over Height	16.75" (42.5 cm)
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Residential
	Frame	Lifetime
	Parts	10 Years
	Labor	1 Year

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.













