



www.tuffstufffitness.com



LWH: 59 x 37 x 54 in/150 x 94 x 137 cm  
WT: 85 lb/39 kg

## LIGHT COMMERCIAL WARRANTY

- TEN (10) YEARS:** Structural main frames, welds, cams and weight plates.
- FIVE (5) YEARS:** Pivot bearings, pulleys, bushings, guide rods and gas shocks.
- ONE (1) YEAR:** Cables, linear bearings and pull-pin components.
- SIX (6) MONTHS:** Upholstery, finish and rubber grips.
- ALL OTHER PARTS** not mentioned elsewhere in the warranty will expire one (1) year from the date of purchase to the original purchaser.

**Light Commercial Use:** Light Commercial warranty applies only to facilities like hotels, apartment complexes, personal training studios, fire & police stations, etc. where the equipment would be used by no more than 30 people per day.

# EVOLUTION

LIGHT COMMERCIAL STRENGTH

## CAB-335 ADJUSTABLE ABDOMINAL BENCH

- 11-position adjustable exercise intensity from 30° angle to flat.
  - Built in handle for performing reverse abdominal exercises.
  - Comfortable padded foot supports.
  - Transport wheels allow easy roll-away.
  - Maximum weight: 400 lb/181 kg
- 
- **FRAME MATERIALS:** 2x3" 11-gauge oval & rectangular tubular steel frames with a combination of 2x2" round tubing.
  - **WELDS:** All welded construction by inert-gas MIG welding conforming with all Structural Welding Code-Steel Standards and Specifications.
  - **FINISH:** Electrostatically applied powder coat finish.
  - **FRAME COLORS:** Main frame: Platinum Sparkle Accent: Cathedral Gray
  - **UPHOLSTERY:** Black, premium grade naugahyde formulated to resist bacteria, stains, mildew and oil. Meets most flammability test requirements. Double-stitched with "hidden" borders.
  - **PADDING:** High density 2" thick rebond urethane foam glued to 1" industrial plywood backing, trimmed and formed to exact fit.
  - **ADJUSTMENT PINS:** 1/2" push-pull spring loaded solid steel adjustment pins with ultimate load of 9040 lbs. and 46042 psi sheer strength.
  - **BEARINGS:** 1" solid steel pivot axles with non-friction 2" sealed bearings (load rating of 2400 lbs.) internally encased on primary pivots, and oil-impregnated bronze bushings on all secondary pivots.
  - **GUIDE RODS:** 3/4" solid steel 1045 (tgp) hard chrome finish.
  - **CABLES:** 3/16" and 1/8" USA-Made/Certified EXERFLEX PRO® high performance fitness cable.
  - **PULLEYS:** 4-1/2" and 3-1/2" fiberglass-impregnated nylon pulleys with double sealed roller bearings.
  - **SELECTOR WEIGHT PINS:** Solid steel, magnetic with ball-end to ensure a tight connection and secure fit. Coiled lanyard helps prevent pin removal and loss.
  - **FASTENERS:** All frame bolts and nuts are 3/8" and 1/2" zinc oxide.
  - **WEIGHT STACK:** Solid steel weight plates with self aligning low friction sleeves.