





## PREMIUM FITNESS EQUIPMENT SINCE 1981

## 650 TREADMILL

With a combination of the latest technology options and the reliability of TRUE's premium warranty, the C650 treadmill provides the performance and efficiency needed for your commercial facility. Patented items like HRC Heart Rate Control® and TRUE's low-impact Soft System® allows your users to have a first-class exercise experience. In addition, a variety of consoles are available to provide multiple levels of features, technology, and asset management.





## **C650 TREADMILL**

Power Source	110V/20A, 220V Option Available
Cord Length	12' / 3.7 M
Drive Motor	5 HP AC Self-Cooling Max Drive
Power Factor Correction (PFC)	Standard
Incline Motor	1,200 lbs. of Thrust
Speed Sensor	Optical
Deck	Reversible 1" / 0.8 cm Medium-Density Fiberboard
Reversible Deck	Standard
Belt	Siegling Multi-Ply with PVC Coating
Rollers	3" / 8 cm w/ Shielded Bearings
Impact System	True Soft System®
Frame Construction	Robotically Welded Heavy-Gauge Steel
Lubrication	Silax
Speed Range	0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)
Incline/Decline Range	0% to 15%, ( -3% to 15% with Decline)
Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point
Handrail Design	Extended Handrails with Molded Rubber, Moisture Resistant Grips
Contact Heart Rate Monitoring	Yes
Wireless Heart Rate Monitoring	Polar®
	Transcend <sup>16</sup> , Escalate <sup>15</sup> , Escalate <sup>9</sup> , Emerge
Saftey Clip	Standard/Non-Removable
Extended Handrails	Standard
Large Straddle Covers	Standard
User Detection	User Present Detection™
	ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC
Accessories	Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder, Power Cord Management, Optional Medical Rails, Optional Decline Feet Kit
Footprint	82" L x 33" W x 60.3" H / 208.2 cm x 83.8 cm x 153.1 cm
Footprint with Decline	82" L x 33" W x 62.5" H / 208.2 cm x 83.8 cm x 158.7 cm
Running Surface  Machine Weight Shipping Weight Maximum User Weight Step-Up Height Portability	60" L x 22" W / 152.4 cm x 55.8 cm
	428 lbs /194.1 kg
	470 lbs / 213.1 kg
	500 lbs / 226.7 kg
	7" / 17.7 cm (9" / 22.8 cm with Optional Decline)
	2 Front Transport Wheels
Warranty Type	Commercial (all dues paying facilities, regardless of usage)
	Lifetime
	5 Years
	3 Years
Labor	3 Years
	Cord Length Drive Motor Power Factor Correction (PFC) Incline Motor Speed Sensor Deck Reversible Deck Belt Rollers Impact System Frame Construction Lubrication Speed Range Incline/Decline Range Quick Access Control Handrail Design Contact Heart Rate Monitoring Wireless Heart Rate Monitoring Wireless Heart Rate Monitoring Extended Handrails Large Straddle Covers User Detection Accessories Footprint Footprint with Decline Running Surface Machine Weight Shipping Weight Maximum User Weight Step-Up Height Portability Warranty Type Frame Motor Parts

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

