

650 TREADMILL

With a combination of the latest technology options and the reliability of TRUE's premium warranty, the C650 treadmill provides the performance and efficiency needed for your commercial facility. Patented items like HRC Heart Rate Control® and TRUE's low-impact Soft System® allows your users to have a first-class exercise experience. In addition, a variety of consoles are available to provide multiple levels of features, technology, and asset management.



FEATURES

- 15.0 MPH (24 KPH) Maximum speed with 15% Maximum incline
- Patented HRC Cruise Control® and Soft System® deck
- Reversible Deck

SPECIFICATIONS

DIMENSIONS (L X W X H)

82" x 33" x 60.3" / 208.28 cm x 83.82 cm x 153.16 cm

SPEED

0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)

INCLINE/DECLINE LEVELS

0% to 15%, (-3% to 15% with Decline)

PRODUCT WEIGHT

428 lbs / 194.1 kg

COLOR

Charcoal/Black



CONSOLE OPTIONS



ENVISION



ENVISION
WITH
COMPASS



EMERGE



ESCALATE



IGNITE

PREMIUM 650 SERIES



C650 TREADMILL

TECHNICAL SPECIFICATIONS	Power Source	120V/20A (NEMA 5-20R receptacle) 230V/15A
	Cord Length	12' / 3.7 M
	Drive Motor	5 HP AC Self-Cooling Max Drive
	Power Factor Correction (PFC)	Standard
	Incline Motor	1,200 lbs. of Thrust
	Speed Sensor	Optical
	Deck	Reversible 1" / 2.54 cm Medium-Density Fiberboard
	Reversible Deck	Standard
	Belt	Lubricant Infused Siegling Multi-Ply with PVC Coating
	Rollers	3" / 8 cm w/ Shielded Bearings
	Impact System	True Soft System®
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	Silax
	Speed Range	0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)
	Incline/Decline Range	0% to 15%, (-3% to 15% with Decline)
	Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar®
	AVAILABLE CONSOLES	Envision ¹⁶ with Compass, Envision ¹⁶ , Escalate ⁹ , Emerge, Ignite
ASSET TRACKING	EcoFit Compatible	
SAFETY	Safety Clip	Standard/Non-Removable
	Extended Handrails	Standard
	Large Straddle Covers	Standard
	User Detection	User Present Detection™
REGULATORY APPROVALS	ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC	
EXTRAS	Accessories	Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder, Power Cord Management, Optional Medical Rails, Optional Decline Feet Kit
PHYSICAL SPECIFICATIONS	Footprint	82" L x 33" W x 60.3" H / 208.28 cm x 83.82 cm x 153.16 cm
	Footprint with Decline	82" L x 33" W x 62.5" H / 208.28 cm x 83.82 cm x 158.75 cm
	Running Surface	60" L x 22" W / 152.4 cm x 55.8 cm
	Machine Weight	428 lbs / 194.1 kg
	Shipping Weight	470 lbs / 213.1 kg
	Maximum User Weight	500 lbs / 226.7 kg
	Step-Up Height	7" / 17.7 cm (9" / 22.86 cm with Optional Decline)
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (all dues paying facilities, regardless of usage)
	Frame	Lifetime
	Motor	5 Years
	Parts	3 Years
	Labor	3 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.