# TRUE

## **200 TREADMILL**

The C200 Treadmill provides your commercial facility reliable performance and a high-quality experience with patented features like HRC Heart Rate Control® and TRUE'S low-impact Soft System®. In addition, the 200 treadmill is the ideal choice for rehabilitation use at health and medical facilities with a low speed of only .2 mph.

#### **FEATURES**

- LCD Console Screen
- Extended handrails
- Patented HRC Cruise Control®
- TRUE Soft System® deck

#### **SPECIFICATIONS**

#### **DIMENSIONS** (L X W X H)

83.5" x 32" x 60.5" / 212.09 cm x 81.2 cm x 153.67 cm

#### **SPEED**

0.2 to 12.0 MPH / 0.3 to 19 KPH

#### **INCLINE/DECLINE LEVELS**

0% to 15%

#### **PRODUCT WEIGHT**

349 lbs / 158.3 kg

#### **COLOR**

Silver



#### **CONSOLE OPTIONS**



### TWO WINDOW LCD DISPLAY

Standard two window LCD display console featuring 12-15 programs, HRC Heart Rate Control® cruise control, CSAFE power.

## 200 SERIES



#### CS200 TREADMILL

TECHNICAL SPECIFICATIONS	Power Source	120V/20A (NEMA 5-20R receptacle) 230V/15A
	Cord Length	10' / 3.0 M
_	Drive Motor	4 HP AC Endura-Drive
_	Incline Motor	1,000 lbs. of thrust
	Speed Sensor	Optical
	Deck	1" / 2.54 cm Medium Density Fiberboard
	Belt	Lubricant Infused Siegling Multi-Ply with PVC Coating
	Rollers	3" / 8 cm w/ Sealed Bearings
	Impact System	True Soft System®
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	Silax
	Speed Range	0.5 to 12.0 MPH / 0.8 to 19.3 KMH
	Incline/Decline Range	0% to 15%
	Quick Access Control	Speed, Incline, Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
CONSOLE	Display	LCD
	Programs	12
	HRC Workouts	1
	HRC Cruise Control	Standard
	CSAFE Power	Standard
	Diagnostic	Standard
SAFETY	Safety Clip	Standard
	Extended Handrails	Standard
	Large Straddle Covers	Standard
REGULATORY APPROVAL	S	ETL, UL1647, CSA, (CE for 220 v)
PHYSICAL SPECIFICATIONS	Footprint	83.5" L x 32" W x 60.5" H / 212.09 cm x 81.2 cm x 153.67 cm
	Running Surface	60" L x 22" W / 1524 cm x 55.88 cm
	Machine Weight	349 lbs / 158.3 kg
	Shipping Weight	424 lbs / 192.3 kg
	Maximum User Weight	350 lbs / 158.7 kg
	Step-Up Height	6.25" / 15.88 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)
	Frame	Lifetime
	Motor	5 Years
_	Parts	5 Years
	Labor	1 Year

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

