TRUE

600 TREADMILL

With a combination of the latest technology options and the reliability of TRUE's premium warranty, the C600 treadmill provides the performance and efficiency needed for your commercial facility. HRC Heart Rate Control® and TRUE's low-impact Soft System® allows your users to have a first-class exercise experience. In addition, a variety of consoles are available to provide multiple levels of features, technology, and asset management.

Optional medical handrails available

FEATURES

- Maximum Incline: 15%
- Maximum Speed: 12 MPH (19 KPH)
- HRC Cruise Control® and Soft System® Deck
- Reversible deck
- Optional medical handrails
- Multiple console options available

SPECIFICATIONS

DIMENSIONS (L X W X H)

79" x 31.5" x 62" / 200.66 cm x 80.01 cm x 157.48 cm

SPEED

0.2 to 12 MPH / 0.3 to 19 KPH

INCLINE/DECLINE LEVELS

0% to 15%

PRODUCT WEIGHT

349 lbs / 158.3 kg

COLOR

Charcoal/Black



CONSOLE OPTIONS



ENVISION SHOW



SHOWRUNNER



ENVISION II 9" Touchscreen



EMERGE II



IGNITE II



C600 TREADMILL

JUUU IIKLADIVIILL		
TECHNICAL SPECIFICATIONS	Power Source	120V/20A Dedicated (NEMA 5-20 Receptacle) 230V/15A Option Available
	Cord Length	12' / 3.7 M
	Drive Motor	5 HP AC Self-Cooling Max Driver
	Motor Controller	PFC
	Incline Motor	1,200 lbs. of thrust
	Speed Sensor	Optical
	Deck	Waxed
	Reversible Deck	Standard
	Belt	Maintenance free, low-amp draw pre-waxed Medex deck and TPU belt system
	Rollers	3" / 8 cm w/ Shielded Bearings
	Impact System	True Soft System®
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Speed Range	0.2 to 12 MPH / 0.3 to 19 KPH
	Incline/Decline Range	0% to 15%
	Quick Access Control	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Moisture-Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar®
AVAILABLE CONSOLES		Envision, ShowRunner, Envision II 9", Emerge II, Ignite II
ASSET TRACKING		EcoFit Compatible
SAFETY	Safety Clip	Removable
	Extended Handrails	Standard
	Large Straddle Covers	Standard
	User Detection	Person Present Detection
REGULATORY APPROVALS		ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC
EXTRAS	Accessories	Water Bottle Holder (2), Accessory Tray, Tablet Holder, Optional Medical Handrails
PHYSICAL SPECIFICATIONS	Footprint	79" L x 31.5" W x 62" H / 200.66 cm x 80.01 cm x 157.48 cm
	Running Surface	60" L x 22" W / 152.4 cm x 55.88 cm
	Machine Weight	349 lbs / 158.3 kg
	Shipping Weight	424 lbs / 192.3 kg
	Maximum User Weight	400 lbs / 181.4 kg
	Step-Up Height	6.5" / 16.51 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (all dues paying facilities, regardless of usage)
	Frame	Lifetime
	Motor	5 Years
	Parts	3 Years
	Labor	3 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

